



KISO 141 EPDM, 3-top, 4-top, L and crown profiles

KISO 141 EPDM is an extruded EPDM closed cellular rubber sealing strip with a glass fibre scrim carrier tape, which is used by the window industry to ensure water and air tightness in windows and by numerous builders and craftsmen when renovating older wooden windows and doors to ensure draught exclusion.

An easy and reliable solution, approved by MTK*, Sweden

Mounting of KISO 141 EPDM ensures water and air tightness between frame and insulating glass and between insulating glass and beads in wooden windows and conservatories. KISO 141 EPDM is equally applicable for factory and on site glazing.

KISO 141 EPDM is supplied in numerous profiles and dimensions and in several colours – to suit your needs. The glass fibre scrim carrier tape ensures strong adhesion to dry, smooth surfaces like wood, metal and glass. On request the profiles may be supplied without tape.

In old wooden windows and doors KISO 141 EPDM seals gaps, excluding draught whereby significant energy savings and improved indoor climate are achieved.



KISO 141 EPDM 4-top, black



KISO 141 EPDM hollow profile, black

Advantages

- Approved by MTK*, Sweden
- Approved by RISE according to P-marking regulations
- UV resistant
- Excellent ozone resistance
- Glass fibre scrim carrier tape for extra strength
- Excellent adhesiveness to dry and smooth surfaces (e.g. wood, metal and glass)
- Air tight – draught excluder and energy saver
- Water tight – water absorption is negligible
- Very good resistance to solvents
- Simple, quick and clean mounting
- Very good aging properties

*MTK is a committee created and "owned" by the glass manufacturers and the glaziers associations in Sweden. MTK is testing and approving glazing materials for installation of Insulated Glass Units. For suppliers to Scandinavian window manufacturers approval from MTK is a prerequisite.