



## KISO 512 FLEECE-BUTYL

KISO 512 FLEECE-BUTYL is developed for water sealing in kitchens, bathrooms and other wet rooms. It is a rubber based extruded and self-adhesive butyl laminated with a polypropylene based non-woven fleece, supplied as strip or as pads to form a pipe collar.

### Sealing and reinforcing

In kitchens, bathrooms and other wet rooms, KISO 512 FLEECE-BUTYL is primarily used for water sealing between the floor and wall, wall sections and around drainage points and pipes..

The high performance butyl ensures a water tight seal and to make for easy application, KISO 512 FLEECE-BUTYL can be supplied with an overlapping liner paper for a two-step application along corners.

The non-woven fleece will accept cement, plaster and paint, also making KISO 512 FLEECE-BUTYL ideal for sealing and reinforcing cracks in walls before plastering.

The adhesive qualities of the butyl, combined with a strong non-woven fleece makes KISO 512 FLEECE-BUTYL suitable for the sealing of joints in roofing and of most buildings and constructions to prevent air-leakage.



*KISO 512 FLEECE-BUTYL; pipe collar with overlapping liner paper*



*KISO 512 FLEECE-BUTYL; strip*

### Advantages

- Water tight seal
- Airtight
- Strong, reinforcing non-woven fleece
- Accepts plaster and paint
- Strong, long-term adhesion to concrete, wood, metal and glass
- The butyl is non hardening – remains flexible throughout service life
- Highly adhesive
- Simple, quick and safe installation